




Material : Phosphor Bronze



P/N	Wire Gauge	Insulation Diameter	Finish	Reel Q'TY
CP35TN21PES	AWG #20~#24	2.50 .098 MAX.	2.03µm (80µinch) Min. Tin-lead over 0.76µm (30µinch) Nickel	12,000 PCS
CP35TN2APES	AWG #20~#24	2.50 .098 MAX.	Selective gold flash on surface contract area over 1.27µm (50µinch) Nickel	12,000 PCS
CP35TN2BPES	AWG #20~#24	2.50 .098 MAX.	Selective 0.38µm (15µinch) gold on surface contract area over 1.27µm (50µinch) Nickel	12,000 PCS
CP35TN2CPES	AWG #20~#24	2.50 .098 MAX.	Selective 0.76µm (30µinch) gold on surface contract area over 1.27µm (50µinch) Nickel	12,000 PCS

	DATE	1-31-00	UNIT: mm / inch	TITLE:	 瀚荃股份有限公司 CvILUX Corporation		
	DRAWN BY:	David	TOLERANCE UNLESS OTHERWISE SPECIFIED X ±0.20/.008 X' ± 1" XX ±0.10/.004 X' ± XXX ±0.05/.002 XX' ±	MATERIAL:			
	ENGINEER:	David		CP35 FEMALE CRIMP TERMINAL			
	CHECKED BY:	Amey	APPROVED BY:	Amey		FINISH:	
SYM	NAME	DATE	REVISIONS	DRAWING NO.	CP3503SC	PART NO.	CP35TN2*PES
				SCALE	6 / 1	SHEET	1 OF 1