

Ordering Code

① **CD 7 3** ② **2 5** ③ **P** ④ **2** ⑤ **1** ⑥ **0 0**

① Series No.

② Contacts:

9,15,25,37

③ Connector type:

P= Plug (Male)

S= Receptacle(Female)

④ Plating code:

2=Gold flash plated over Nickel

3=15 μ in Gold plated over Nickel

4=30 μ in Gold plated over Nickel

5=50 μ in Gold plated over Nickel

⑤ Insulator Color:

1=Black, 0=White.

⑥ Other option:

00= With \varnothing 3.05mm holes on shell(Standard)

K0= Riveted #4-40 UNC open nuts on rear shell

K1= Riveted M3x0.5 open nuts on rear shell

I 0= Riveted ground tabs thread #4-40 UNC open and ground tabs with \varnothing 3.2mm holes

I 2= Riveted ground tabs thread M3x0.5 open and ground tabs with \varnothing 3.2mm holes

I 1= Riveted ground tabs thread #4-40 UNC open and ground tabs with board lock

I 3= Riveted ground tabs thread M3x0.5 open and ground tabs with board lock

F0= Riveted ground hooks with #4-40 UNC open

F1= Riveted ground hooks with M3x0.5 open

J0= Assembly ground hooks by #4-40 UNC Hex screws

J1= Assembly ground hooks by M3x0.5 Hex screws

P0= Riveted #4-40 UNC open nuts on front shell

P1= Riveted M3x0.5 open nuts on front shell

*Special option Consult manufacturer